

PS6509

15" Fanless POS Terminal with Intel® Atom™ processor N270 Platform



 Zoom

FEATURES

- > Intel® Atom™ processor N270 Platform
- > 15" LCD display with touch screen
- > Flexible design for versatile applications
- > Fanless POS terminal
- > Optional i-Button for user identification & security control
- > Optional 802.11 b/g WLAN communication capability
- > Easy to be transferred to panel PC as long as removing the stand

Specifications

>> Systems

CPU Support	Intel® Atom™ N270 1.6GHz
EMC & Safety	CE/ FCC/ cUL/ CB
Memory	1 x DDRII SO-DIMM Slot, 512M DDRII SDRAM (Up to 2GB)
Core Logic	Intel® 945GSE & ICH7M support FSB 533, DDRII 533
Network	Giga Fast Ethernet (optional 802.11 b/g WLAN Mini-PCI module)
Power Supply	72 watt ~ 120 watt power adaptor
System Weight	11 kg
Dimension (W x H x D)	365 x 363 x 303 mm (14.37" x 14.29" x 11.92")
O.S. Support	WINXP, POSReady2009, WEPOS, WES2009, WIN7, POSReady7
HDD	1 x 2.5" SATA HDD
CF	1 x Compact Flash slot for CF type I/O storage (on board with IDE interface)

>> I/O Ports

Parallel Port	1 x Parallel port (SPP/EPP/ECP)
---------------	---------------------------------

USB 5 x USB 2.0 port (4 on I/O port, 1 on the side of the back cover)

Serial Port 3 x DB-9 (COM 1/2/3), 1 x RJ45 (COM 4), +5/12V Selectable

Keyboard & Mouse 2 x PS/2 port

LAN 1 x Giga Fast Ethernet

Audio 1 x Line-out / 1 x Mic-in

VGA 1 x DB-15 VGA Interface

Cash Drawer 2 x RJ11 port, 12V/24V selectable

>> Display

LCD 15" TFT LCD

Max. Resolution 1024 x 768

Brightness 250 cd/m²

Touch Screen 5-wire Analog resistive

Tilt Angle 0 ~ 70 degree

>> Environment

Operation Temperature 0°~35°C(32°~95°F)

Storage Temperature -20°~60°C(-4°~140°F)

Humidity 20~90%

Highlights

Options:

Water proof front panel (w/o MSR) **Fingerprint Module**



Easy MSR maintenance

Easy 2.5" SATA HDD maintenance



2nd Display (12")



VFD Pole Display

