



*Hopitality / Fast Food / Table Service*



*Transportation / Airline Counters*



*Financial / Banking*



*Medical*

## *Commercial Grade LCD Touch Monitor*



- Rugged and Solid Base Design
- Great Cable Management
- Spill Resistant Commercial Grade Housing
- 15" TFT Active Matrix LCD
- Standard Integrated Triple Track MCR
- Optional Integrated Triple Track MCR *with* Fingerprint Reader
- On Screen Display
- Hidden Power Switch and Control Panel
- 5-Wire Resistive Touch
- USB Touch Screen Interface
- VGA Video Interface
- Easily Wall Mountable



# SPM-T15 LCD Touch Screen Monitor



**Integrated Triple Track Card Reader Standard**



**Hidden Liquid Resistant Control Panel**



**Discreet, Yet Easy to Access Ports**



**SPM-T15 Monitor, MCR, Power Supply and Cord, VGA Cable, USB Cable, Installation Guide and Blank Name Plate Cover**

## Options and Upgrades

Configure your system with these easy to add options:

- Integrated Triple Track MCR with Fingerprint Reader
- Wall Mount Brackets with Standard VESA Configuration

## Applications

The flexible SPM-T15 can be combined with a PC to create a distributed workstation for use in applications like these:

- Airline Counters
- Auto Parts
- Automotive Services
- Book Stores
- Convenience Stores
- Digital Signs
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- License Issue
- Medical
- Message Stations
- Municipalities
- Point of Sale
- Quick Service Restaurant
- Rental Car Counters
- Retail Scanning
- Self Service
- Streaming Video
- Table Service Restaurant
- Training
- Touch Kitchen Video
- Unattended Workstations

## Specifications

<b>Display LCD:</b>	15" TFT Active Matrix LCD
<b>Resolution:</b>	1024 x 768
<b>Brightness:</b>	250 cd/m <sup>2</sup>
<b>Touch Panel:</b>	5-Wire Resistive Touch
<b>MCR:</b>	Integrated USB Interface Triple Track MCR
<b>Colors:</b>	16.2 Million
<b>Contrast Ratio:</b>	500:1
<b>Adjustable Angle:</b>	0° to 90°
<b>Viewing Angle:</b>	H = 150° V = 130° (Left:75° / Right:75° / Up:70° / Down: 60°)
<b>Input Signal:</b>	Analog RGB
<b>Serial Port:</b>	Not Applicable
<b>USB Port – External:</b>	Touchscreen (Penmount 6000 Controller : C8051F321) /
<b>Internal:</b>	MCR
<b>Keyboard Port:</b>	Not Applicable
<b>VGA Port:</b>	One D-Sub 15-Pin
<b>DVI Port:</b>	Not Applicable
<b>Operating Temperature:</b>	32° to 104°F (0° to 40°C)
<b>Humidity:</b>	10% to 90% (Non-Condensing)
<b>Wall / Ceiling Mount:</b>	VESA Holes 75 x 75mm
<b>Power Supply:</b>	DC 12V (3.33A) External Power Adapter
<b>Current/Power Usage:</b>	0.25A / < 30W
<b>Overall Dimensions:</b>	13-7/8"W x 12"H x 8-5/8"D
<b>Carton Dimensions:</b>	18-1/2"W x 11"H x 15-7/8"D
<b>Product Weight:</b>	9.73 lbs.
<b>Shipping Weight:</b>	11 lbs.
<b>Safety and EMI:</b>	CE, FCC, RoHS

The monitor's sturdy base is reinforced with aluminum, adding weight for strength, stability, and reliability. Optional VESA wall mount brackets are designed for multiple mounting options. Where wall mounting is desired the SPM-T15 can be purchased without the base.



**SPM-T15's Sturdy Base**



**Optional SPM-T15 Wall Mount Bracket**



**Other VESA Wall and Ceiling Mount Brackets Available**

All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features/specifications are subject to change without notice.

© 2011, Printed in U.S.A.

Lit-175